Vetrospace L/L+

Pod for up to 6 people

A VETROSPACE IS MORE THAN JUST A POD – IT'S A PRODUCTIVE, PRIVATE, AND SAFE SPACE FOR WORKING, MEETING, AND COLLABORATING.

Spacious enough to act as a large meeting room or a customer service point, the VETROSPACE L pod is a comfortable, soundproof space that will keep everyone feeling refreshed and ready to work. You can design and furnish this acoustic office pod according to your needs from a variety of options.

Materials and finishing

Exterior material is LP-laminate and 16,7 mm sound-controlled safety glass. Laminates in 6 standard colors, plus options for custom colors. Interior is acoustic ECOfelt lining, with 5 standard colors and >50 additional colors.

Dimensions	L	L+
Width	310 cm	260 cm
Depth Height	210 cm 240 cm	260 cm 240 cm
Weight	1300 kg	1380 kg



Vetrospace L/L+

Pod for up to 6 people

Datasheet

Spacious enough to act as a large meeting room or a customer service point, the VETROSPACE L pod is a comfortable, soundproof space that will keep everyone feeling refreshed and ready to work. You can design and furnish this acoustic office pod according to your needs from a variety of options.

Structural option number defines the locations of solid and glass walls. By changing this, you can populate each and every corner, hallway and other space of the room with perfectly matching pod.

Wide and space efficient dual panel sliding door can be placed anywhere on the glass wall.



VETROSPACE Optional accessories:

- Electromagnetic locking
- Control unit RFID
- Door opening button
- Additional sliding door

- AV ready for the wall
- AV readiness for electrical panel
- Air conditioner with remote control
- Automatic fire extinguisher system

TECHNICAL SPECS L & L+

Exterior dimensions L W310 / D210 / H240 cm | L+ W260 / D260 / H240

Exterior material LP-laminate

Interior dimensions L W300 / D200 / H220 cm | L+ W250 / D250 / H220L

Interior material Acoustic ECOfelt lining

Weight L 1300 kg | L+ 1380kg

Indoor surface area $L 6 m^2 \mid L + 6.2 m^2$

Installation height

recquirement >250 cm | >98.5 in

Fire safety UL 723: Class A-C (surface)

ASTM E648:Class 1 (flooring)

Electrical safety IEC 60335-1:2020 | UL 962 (E514776)

Seismic safety Special SEISMIC Certification (2019-0176-COC-01-00)

International Building Code (IBC) 2018 (23.02.2021)
California Building Code (CBC) 2019 (23.02.2021)

Door Patented sliding door

Glass thickness 16.7 mm | 0.66 in sound-control safety glass

Sound reduction STI: 0,03–Ds: 31,3dB (Can. 43-46dB Rw, Lab.) (ISO 23351-1)

Ventilation system Advanced two-stage air filtering-coarse and HEPA

Air flow L Max 100l/s | L+ Max 120l/s

Pressure Positive air pressure

Lighting VLD antimicrobial LED lighting

Power supply 110-240 VAC / 16 A / 50-60 Hz

Power 100 W average, 550 W maximum

Power sockets 4 as standard

^{*} The pod is equipped with smart CO2 based ventilation control, typical value is based on average occupancy & CO2 exhaled by users and will vary based on measured value real time.





Vetrospace L & L+

