

Vetrospace M

Pod ideal for 1-3 people

A VETROSPACE IS MORE THAN JUST A POD – IT'S A PRODUCTIVE, PRIVATE, AND SAFE SPACE FOR WORKING, MEETING, AND COLLABORATING.

Steer clear of distractions with an open-space workstation. The VETROSPACE M can easily accommodate up to three people for a meeting and is also great as a small private office space or breakout room. You can design and furnish it according to your needs from a variety of options.

Materials and finishing

Exterior material is LP-laminate and 16,7 mm sound-controlled safety glass. Laminates in 6 standard colors, plus options for custom colors.

Interior is acoustic ECOfelt lining, with 5 standard colors and >50 additional colors.

Dimensions

Width	210 cm
Depth	160 cm
Height	240 cm
Weight	900 kg



Vetrospace M

Pod ideal for 1-3 people

Datasheet

Steer clear of distractions with an open-space workstation. The VETROSPACE M can easily accommodate up to three people for a meeting and is also great as a small private office space or breakout room. You can design and furnish it according to your needs from a variety of options.

Structural option number defines the locations of solid and glass walls. By changing this, you can populate each and every corner, hallway and other space of the room with perfectly matching pod.

Wide and space efficient dual panel sliding door can be placed anywhere on the glass wall.



VETROSPACE Optional accessories:

- Electromagnetic locking
- Control unit RFID
- Door opening button
- Additional sliding door
- AV ready for the wall
- AV readiness for electrical panel
- Air conditioner with remote control
- Automatic fire extinguisher system

TECHNICAL SPECS

Exterior dimensions

W210 / D160 / H240 cm | W82.7 / D63 / H94.5 in

Exterior material

LP-laminate

Interior dimensions

W200 / D150 / H220 cm | W78.7 / D59 / H86.6 in

Interior material

Acoustic ECOfelt lining

Weight

900 kg | 1950 lbs

Indoor surface area

43m² | 32.2 ft²

Installation height requirement

>250 cm | >98.5 in

Fire safety

UL 723: Class A-C (surface)
ASTM E648: Class 1 (flooring)

Electrical safety

IEC 60335-1:2020 | UL 962 (E514776)

Seismic safety

Special SEISMIC Certification (2019-0176-COC-01-00)
International Building Code (IBC) 2018 (23.02.2021)
California Building Code (CBC) 2019 (23.02.2021)

Door

Patented sliding door

Glass thickness

16.7 mm | 0.66 in sound-control safety glass

Sound reduction

STI: 0,03–Ds: 31,3dB (Can. 43-46dB Rw, Lab.) (ISO 23351-1)

Ventilation system

Advanced two-stage air filtration (coarse and HEPA 13)

Air flow

Max 60l/s

Pressure

Positive air pressure

Lighting

VLD antimicrobial LED

Power supply

110-240 VAC / 16 A / 50-60 Hz

Power

70 W average, 300 W maximum

Power sockets

4 as standard

* The pod is equipped with smart CO2 based ventilation control, typical value is based on average occupancy & CO2 exhaled by users and will vary based on measured value real time.



Vetrospace M