

Vetrospace S/S+

Pod ideal for 1-2 people

A VETROSPACE IS MORE THAN JUST A POD – IT'S A PRODUCTIVE, PRIVATE, AND SAFE SPACE FOR WORKING, MEETING, AND COLLABORATING.

This compact 2 person meeting pod doubles as a personal space pod for video conferences, phone calls, or private corridor discussions. You can design and furnish it according to your needs from a variety of options.

Materials and finishing

Exterior material is LP-laminate and 16,7 mm sound-controlled safety glass. Laminates in 6 standard colors, plus options for custom colors.

Interior is acoustic ECOfelt lining, with 5 standard colors and >50 additional colors.

Dimensions	S	S+
Width	210 cm	210 cm
Depth	110 cm	130 cm
Height	240 cm	240 cm
Weight	760 kg	795 kg



Vetrospace S/S+

Pod ideal for 1-2 people

Datasheet

This compact 2 person meeting pod doubles as a personal space pod for video conferences, phone calls, or private corridor discussions. You can design and furnish it according to your needs from a variety of options.

Structural option number defines the locations of solid and glass walls. By changing this, you can populate each and every corner, hallway and other space of the room with perfectly matching pod.

Wide and space efficient dual panel sliding door can be placed anywhere on the glass wall.



VETROSPACE Optional accessories:

- Electromagnetic locking
- Control unit RFID
- Door opening button
- Additional Interior sliding door
- AV ready for the wall
- AV readiness for electrical panel
- Air conditioner with remote control
- Automatic fire extinguisher system

TECHNICAL SPECS

Exterior dimensions

Exterior material

Interior dimensions

Interior material

Weight

Indoor surface area

Installation height requirement

Fire safety

Electrical safety

Seismic safety

Door

Glass thickness

Sound reduction

Ventilation system

Air ventilation

Pressure

Lighting

Power supply

Power

Power sockets

S & S+

S: W210 / D110 / H240 cm, S+: W210 / D130 / H240

LP-laminate

S: W200 / D100 / H220 cm, S+: W200 / D120 / H220

Acoustic ECOfelt lining

S 760kg | S+ 795kg

S 2m² | S+ 2.4m²

>250 cm | >98.5 in

UL 723: Class A-C (surface)
ASTM E648: Class 1 (flooring)

IEC 60335-1:2020 | UL 962 (E514776)

Special SEISMIC Certification (2019-0176-COC-01-00)
International Building Code (IBC) 2018 (23.02.2021)
California Building Code (CBC) 2019 (23.02.2021)

Patented sliding door

16.7 mm | 0.66 in sound-control safety glass

STI: 0,03 – Ds: 30,6dB (Can. 43-46dB Rw Lab.) (ISO 23351-1)

Advanced two-stage air filtering (coarse and HEPA)

Max 40l/s

Positive air pressure

VLD antimicrobial LED

110-240 VAC / 16 A / 50-60 Hz

50W average, 150W maximum

4 as standard

* The pod is equipped with smart CO2 based ventilation control, typical value is based on average occupancy & CO2 exhaled by users and will vary based on measured value real time.



Vetrospace S