

# Vetrospace XL

Pod for up to 8 people

A VETROSPACE IS MORE THAN JUST A POD – IT'S A PRODUCTIVE, PRIVATE, AND SAFE SPACE FOR WORKING, MEETING, AND COLLABORATING.

Enjoy exceptional sound insulation and air quality in our second-largest pod, which offers plenty of space for up to eight and also works as a cozy private space. You can design and furnish it according to your needs from a variety of options.

## Materials and finishing

Exterior material is LP-laminate and 16,7 mm sound-controlled safety glass. Laminates in 6 standard colors, plus options for custom colors. Interior is acoustic ECOfelt lining, with 5 standard colors and >50 additional colors.

## Dimensions

Width	310 cm
Depth	310 cm
Height	240 cm
Weight	1 600 kg



# Vetrospace XL

Pod for up to 8 people

## Datasheet

Enjoy exceptional sound insulation and air quality in our second-largest pod, which offers plenty of space for up to eight and also works as a cozy private space. You can design and furnish it according to your needs from a variety of options.

Structural option number defines the locations of solid and glass walls. By changing this, you can populate each and every corner, hallway and other space of the room with perfectly matching pod. Wide and space efficient dual panel sliding door can be placed anywhere on the glass wall.



### VETROSPACE Optional accessories:

- Electromagnetic locking
- Control unit RFID
- Door opening button
- Additional sliding door
- AV ready for the wall
- AV readiness for electrical panel
- Air conditioner with remote control
- Automatic fire extinguisher system

## TECHNICAL SPECS

### Exterior dimensions

W310 / D310 / H240 cm

### Exterior material

LP-laminate

### Interior dimensions

W300 / D300 / H220 cm

### Interior material

Acoustic ECOfelt lining

### Weight

1600 kg | 3520 lbs

### Indoor surface area

12 m<sup>2</sup> | 129.1 ft<sup>2</sup>

### Installation height requirement

>250 cm | >98.5 in

### Fire safety

UL 723: Class A-C (surface)  
ASTM E648: Class 1 (flooring)

### Electrical safety

IEC 60335-1:2020 | UL 962 (E514776)

### Seismic safety

Special SEISMIC Certification (2019-0176-COC-01-00)  
International Building Code (IBC) 2018 (23.02.2021)  
California Building Code (CBC) 2019 (23.02.2021)

### Door

Patented sliding door

### Glass thickness

16.7 mm | 0.66 in sound-control safety glass

### Sound reduction

D<sub>s,A</sub> 30-31,5dB (ISO 23351-1), Rw 43-46dB, STI: 0.03

### Ventilation system

Advanced two-stage air filtering-coarse and HEPA

### Air flow

Max 120l/s

### Pressure

Positive air pressure

### Lighting

VLD antimicrobial LED lighting

### Power supply

110-240 VAC / 16 A / 50-60 Hz

### Power

100 W average, 550 W maximum

### Power sockets

4 as standard

\* The pod is equipped with smart CO2 based ventilation control, typical value is based on average occupancy & CO2 exhaled by users and will vary based on measured value real time.



# Vetrospace XL

**ISKU**  
Since 1928



# Vetrospace XL

**ISKU**  
Since 1928