Pod for up to 10 people

A VETROSPACE IS MORE THAN JUST A POD – IT'S A PRODUCTIVE, PRIVATE, AND SAFE SPACE FOR WORKING, MEETING, AND COLLABORATING.

Our largest pod comfortably fits up to 10 people, making it ideal for meetings and encounters. Our uniqueness comes from our sound reduction of +30dB, our two-stage air filtration (G4 prefilter + HEPA-13), our automatic CO2-controlled ventilation and photon disinfection LED lightning.

Materials and finishing

Exterior material is LP-laminate and 16,7 mm sound-controlled safety glass. Laminates in 6 standard colors, plus options for custom colors. Interior is acoustic ECOfelt lining, with 5 standard colors and >50 additional colors.

Dimensions

Width	410 cm
Depth	310 cm
Height	240 cm
Weight	1950 kg



Pod for up to 10 people

Datasheet

Vetrospace's largest pod comfortably fits up to 10 people, making it ideal for meetings and encounters or for when you need plenty of space to spread out and focus on a creative task. This flexible and highly modular soundproof booth is built to last. Design and furnish it according to your needs from a variety of options.

Structural option number defines the locations of solid and glass walls. By changing this, you can populate each and every corner, hallway and other space of the room with perfectly matching pod.

Wide and space efficient dual panel sliding door can be placed anywhere on the glass wall.

2 _5 3 4

VETROSPACE Optional accessories:

- Electromagnetic locking ٠
- Control unit RFID .
- Door opening button ٠
- Additional sliding door ٠

- AV ready for the wall
- AV readiness for electrical panel
 - Air conditioner with remote control
- Automatic fire extinguisher system

TECHNICAL SPECS	XXL
Exterior dimensions	W410 / D310 / H240 cm W161.4 / D122 / H94.5 in
Exterior material	LP-laminate
Interior dimensions	W400 / D300 / H220 cm W157.5 / D118.1 / H86.6 in
Interior material	Acoustic ECOfelt lining
Weight	1950 kg 4300 lbs
Indoor surface area	12 m² 129.1 ft²
Installation height recquirement	>250 cm >98.5 in
Fire safety	UL 723: Class A-C (surface) ASTM E648:Class 1 (flooring)
Electrical safety	IEC 60335-1:2020 UL 962 (E514776)
Seismic safety	Special SEISMIC Certification (2019-0176-COC-01-00)
	International Building Code (IBC) 2018 (23.02.2021) California Building Code (CBC) 2019 (23.02.2021)
Door	
Door Glass thickness	California Building Code (CBC) 2019 (23.02.2021)
	California Building Code (CBC) 2019 (23.02.2021) Patented sliding door
Glass thickness	California Building Code (CBC) 2019 (23.02.2021) Patented sliding door 16.7 mm 0.66 in sound-control safety glass
Glass thickness Sound reduction	California Building Code (CBC) 2019 (23.02.2021) Patented sliding door 16.7 mm 0.66 in sound-control safety glass D _s ,A 30-31,5dB (ISO 23351-1), Rw 43-46dB, STI: 0.03
Glass thickness Sound reduction Ventilation system	California Building Code (CBC) 2019 (23.02.2021) Patented sliding door 16.7 mm 0.66 in sound-control safety glass D _s ,A 30-31,5dB (ISO 23351-1), Rw 43-46dB, STI: 0.03 Advanced two-stage air filtration (coarse and HEPA 13)
Glass thickness Sound reduction Ventilation system Air flow	California Building Code (CBC) 2019 (23.02.2021) Patented sliding door 16.7 mm 0.66 in sound-control safety glass D _s ,A 30-31,5dB (ISO 23351-1), Rw 43-46dB, STI: 0.03 Advanced two-stage air filtration (coarse and HEPA 13) Min 30 I/s, typical 180 I/s* and max 495 (max fan capacity)
Glass thickness Sound reduction Ventilation system Air flow Pressure	California Building Code (CBC) 2019 (23.02.2021) Patented sliding door 16.7 mm 0.66 in sound-control safety glass D _s ,A 30-31,5dB (ISO 23351-1), Rw 43-46dB, STI: 0.03 Advanced two-stage air filtration (coarse and HEPA 13) Min 30 I/s, typical 180 I/s* and max 495 (max fan capacity) Positive air pressure
Glass thickness Sound reduction Ventilation system Air flow Pressure Lighting	California Building Code (CBC) 2019 (23.02.2021) Patented sliding door 16.7 mm 0.66 in sound-control safety glass D _s ,A 30-31,5dB (ISO 23351-1), Rw 43-46dB, STI: 0.03 Advanced two-stage air filtration (coarse and HEPA 13) Min 30 I/s, typical 180 I/s* and max 495 (max fan capacity) Positive air pressure VLD antimicrobial LED

* The pod is equipped with smart CO2 based ventilation control, typical value is based on average occupancy & CO2 exhaled by users and will vary based on measured value real time.







....





